


# MIDLAND FABRIC & BAR Ltd



Channels (Parallel Flanges) – Specifications to BS EN 10025 S275

Size mm (nominal)	Weight Kg/m	Depth of section 'D' mm	Width of section 'B' mm	Thickness (mm)		
				Web 't' mm	Flange 'T' mm	Depth Between Flanges 'd' mm
100x50	10.2	100.0	80.0	5.0	8.5	65.0
125x65	14.8	125.05	65.0	5.5	9.5	82.0
150x75	17.9	150.0	75.0	5.5	10.0	106.0
150x90	23.9	150.0	90.0	6.5	12.0	102.0
180x75	20.3	180.0	75.0	6.0	10.5	135.0
180x90	26.1	180.0	90.0	6.5	12.5	131.0
180x75	23.4	200.0	75.0	6.0	12.5	151.0
200x90	29.7	200.0	90.0	7.0	14.0	148.0
230x75	25.7	230.0	75.0	6.5	12.5	181.0
230x90	32.2	230.0	90.0	7.5	14.0	178.0
260x75	27.6	260.0	75.0	7.0	12.0	212.02
260x90	34.8	260.0	90.0	8.0	14.0	208.0
300x90	41.4	300.0	90.0	9.0	15.5	245.0
300x100	45.5	300.0	100.0	9.0	16.5	237.0
380x100	54.0	380.0	100.0	9.5	17.5	315.0
430x100	64.4	430.0	100.0	11.0	19.0	362.0

## Circular Hollow Sections ( dimensions and kgms)

Specification to BS 6363: 43/26 or ST 37/2 DIN 17.1000

Size O.D(mm)	Wall Thickness (mm)									
	2.0	2.5	3.0	3.5	4.0	5.0	6.0/6.3	8.0	10.0	12.5
21.3			1.43							
26.9		1.50	1.87							
33.7		1.99	2.41		2.93					
42.4	1.99	2.55	3.09		3.79					
48.3	2.27		3.56		4.37	5.34				
60.3		3.56	4.51		5.55	6.82				
76.1			5.75		7.11	8.77				
88.9			6.76		8.38	10.30				
101.6					9.62		14.15			
114.3				9.83		13.50	16.80			
139.7						16.60	20.70	26.00	32.00	
152.4					14.60					
168.3						20.10	25.20	31.60	39.00	
193.7						23.30	29.10	36.06	45.30	55.90

24 HOUR DELIVERY TO ALL AREAS - OPEN 7 DAYS A WEEK

TEL: 01384 572996 / 70648 FAX: 01384 76257